

Photo Linking Software Comparison

A Product Comparison by Electronic Data Solutions

Linking Photos to GPS/GIS Features

Many methods are available for linking digital imagery to GIS features. Some of these are summarized below:

Hotlinking or Hyperlinking – Displays an image when clicking on a GIS feature. Photos are stored somewhere on your PC or network, and each GIS feature stores the photo file path and file name as an attribute or as a dynamic hyperlink. *Advantages:* Hotlinking is built into ESRI ArcGIS Desktop. Dynamic hyperlinking can be used to link multiple photos to one feature. *Disadvantages:* Managing the correct entry of the photo file name for the correct GIS feature in the office or in the field can be time-consuming, cumbersome and error-prone.

ArcPad or TerraSync Camera Tool – Takes pictures using attached camera. *Advantages:* Mapping the feature and taking the photo is all managed in one software application, and it is easy to use on handheld with built-in camera. Reduces opportunity for error by linking photos in the field. *Disadvantages:* If the camera is not built-in, it relies on camera device drivers that are compatible with the operating system. Still have to manage hyperlinks in ArcGIS.

Wind Image Transfer – Uses WiFi to transfer photos from WiFi camera to Trimble handheld running TerraSync or ArcPad. Can be used with a free ArcPad .dll to automatically link photo to feature. *Advantages:* Only costs \$75, and transfers photos more quickly and efficiently than over a Bluetooth connection. Reduces opportunity for error by linking photos in the field. *Disadvantages:* Have to have Ricoh WiFi camera and Trimble handheld. Still have to manage hyperlinks in ArcGIS.

TrimPix Pro System – Uses an “Eye-fi Pro” card inserted in a camera to transfer photos over WiFi to a Trimble handheld running TerraSync or ArcPad. Designed to integrate with TerraSync. *Advantages:* Will work with any digital camera that supports an SDHC card and can be deployed to multiple Trimble handhelds. Reduces opportunity for error by linking photos in the field. *Disadvantages:* Cost of \$199, and must be used with Trimble handheld. Still have to manage hyperlinks in ArcGIS.

Wind Image Software - Links GPS data to digital images and outputs to Google Earth KML and KMZ files, ESRI shapefiles and feature classes, and other formats. Designed primarily for cameras that can geocode photos, such as Ricoh 500 SE, an 8 MP 3x optical zoom rugged camera with built-in Bluetooth and optional WiFi. Can be purchased with built-in, WAAS-enabled SiRF GPS or can connect via Bluetooth to external GPS receivers and laser rangefinders for offsets. The Ricoh camera also allows entry of up to 10 attribute memos for a photo, which can be configured as drop-down lists with included software. The camera has the ability to scan barcodes and store them as memos. It features a GPS-lock function which allows the user to take a position, lock GPS, then move back and take a picture. *Advantages:* Automates the linking of photos to features. Can embed images as raster attributes rather than linked images, which improves portability and use across an enterprise. Can imprint text, logos, GPS and memo data on photo. Can output to file and enterprise geodatabases in ArcGIS and ArcSDE. *Disadvantages:* Need camera that can geocode photos.

GPS-Photo Link Software – Similar to Wind Image when working with the Ricoh 500SE. It also has the capability to link photos based on a time stamp, which will work with nearly any digital camera and any GPS. *Advantages:* Works with wide variety of digital cameras and capable of batch processing photo link based on time rather than file name. Outputs to more file formats than Wind Image. *Disadvantages:* Higher cost than Wind Image and only 90 days of maintenance.

		ArcPad or TerraSync Camera Tool	Wi-Fi Transfer with TerraSync or ArcPad		Wind Image		GPS-Photo Link GIS Pro Series version 5.0
			Wind Image Transfer	TrimPix Pro System	ArcMap	StandAlone	
Hardware support	Windows Mobile support	Trimble Nomad, Juno SB/SC, Yuma ¹	Trimble GeoXH/XT/XM, Juno SB/SC, Nomad G Series		N/A		N/A
	Camera Support	Any Attached ¹	Ricoh Caplio 500SE	Any that supports SDHC	Any camera capable of geocoding images		Any ²
	GPS Support	Any Supported by ArcPad or TerraSync	Any Supported by ArcPad or TerraSync		Built-in or Bluetooth ³		Built-in, Bluetooth or Other ⁴
Field Collection Features	Create Photo Link in Field ⁵	Yes	Yes		Yes		Yes
	Feature Collection	Yes	Yes		Yes		Yes
	GPS Lock ⁶	No	No		Yes		Yes
	Laser offset ⁷	Yes	Yes		Yes		Yes
	Attribute Collection ⁸	Yes	Yes		Yes		Yes
	Real-time DGPS ⁹	Yes	Yes		Yes		Yes
	Post-processed GPS ¹⁰	Yes	Yes		No		Yes ¹¹
	Data Quality Filters ¹²	Yes	Yes		No		Yes ¹¹
	Record Barcode as attribute ¹³	Yes	Yes		Yes		Yes
	Link voice note	Yes ¹⁴	Yes ¹⁴		No ¹⁵		No ¹⁵

¹ This tool in other devices is dependent on camera hardware compatibility with Windows Mobile operating system for direct camera control. If camera cannot be controlled directly by ArcPad, the photo can still be linked to a feature if the camera's software places it in My Documents or a sub-folder (or an SD or CF card).

² Must be able to set time and date on digital camera. Time and date does not need to be displayed on the photo.

³ Ricoh camera can be purchased with or without built-in GPS. Built-in GPS is 12-channel WAAS-enabled SiRF receiver, 2-5 meter accuracy. Camera can connect via Bluetooth to any Bluetooth GPS that outputs the NMEA data string.

⁴ Must record GPS hour, minute, second in order to link with photo. Trimble with TerraSync, Garmin, Magellan, etc.

⁵ In ArcPad and TerraSync, the file name of the photo is linked to the feature. On GPS-enabled cameras, GPS coordinates are embedded in the EXIF file header as photos are taken. In Photo-Link, the link can be based on time stamps from the field.

⁶ Take coordinate of feature, lock GPS, then step back and take picture. This feature is built in to the Ricoh 500SE camera.

⁷ Offset functionality built into TerraSync or ArcPad software. Ricoh 500SE camera connects directly to Bluetooth laser rangefinders to record distance in EXIF file header. Compass direction can be created directly from the GPS/Compass module or entered manually as a memo field. Direction and distance can be used to create offset features, or directional symbols using GPS-Photo Link or Wind Image.

⁸ TerraSync and ArcPad support entry of multiple attributes using pick lists and data entry rules. Consumer GPS units usually do not support attribute entry. Ricoh 500SE supports entry of up to 10 attribute Memos, which can be set up with pick-lists using included List Editor software.

⁹ Dependent on GPS receiver capabilities. All Trimble MGIS receivers are real-time capable, as are most consumer GPS receivers. The Ricoh 500SE with GPS is WAAS-enabled.

¹⁰ TerraSync uses Pathfinder Office or GPS Analyst and base station data to post-process GPS and DGPS positions. Post-processing in ArcPad requires Trimble's GPSCorrect for ArcPad extension, using a Trimble Pathfinder receiver and Pathfinder Office or GPS Analyst software. Post-processing is not possible with most consumer GPS receivers, or with the Ricoh 500SE camera with built-in or external GPS.

¹¹ If data is collected in TerraSync.

¹² Data quality filters include position mode, elevation mask, SNR mask, PDOP mask, HDOP Mask, and so on. ArcPad cannot set SNR mask, elevation mask, or HDOP mask. These can be set in GPSCorrect for ArcPad or TerraSync. Consumer GPS receivers generally have no quality filters. The Ricoh 500SE with built-in GPS does not have quality filters, but quality indicators are displayed on the screen.

¹³ Dependent on attached peripheral devices in the case of TerraSync or ArcPad systems. The Ricoh 500SE can scan bar codes and store them in Memo 1. The Trimble Nomad can also scan barcodes and store them as attributes in TerraSync or ArcPad.

¹⁴ TerraSync can link WAV files if the data dictionary has a File Name attribute set up to store the link. ArcPad does not have this capability.

¹⁵ The Ricoh 500SE camera can record voice notes with pictures, but those cannot be processed with Wind Image or Photo Link.

		ArcPad or TerraSync Camera Tool	Wi-Fi Transfer with TerraSync or ArcPad		Wind Image		GPS-Photo Link GIS Pro Series version 5.0
			Wind Image Transfer	TrimPix Pro System	ArcMap	StandAlone	
Desktop Features	Output to shapefile ¹⁶	Yes	Yes		Yes		Yes
	Output to personal, file and enterprise geodatabase feature class	No	No		Yes	No	Yes
	Embed image as raster attribute in geodatabase	No	No		Yes	No	Yes
	Append to existing shapefile or feature class	No	No		Yes	No	Yes
	Scroll through multiple photos in same location	No	No		No		Yes
	Import Tracklog	Yes	Yes		Yes		Yes
	Output to Google Earth ¹⁷	Yes	Yes		No	Yes	Yes
	Output to HTML Web pages	No	No		No	Yes	Yes
	Output to Word and Text	No	No		No	Yes	Yes
	Output to .csv ¹⁷	Yes	Yes		No	Yes	Yes
	Output to Access .mdb ¹⁷	Yes	Yes		No		Yes
	Output to PDF	No	No		No		Yes
	Imprint GPS Data on Picture ¹⁸	No	No		Yes		Yes
	Output renamed photos ¹⁹	No ²⁰	No		Yes		Yes
	ArcMap Toolbar to process photos	No	No		Yes	No	Yes
	Photo Editing ²¹	No	No		Yes		Yes
	EXIF Data Editing	No	No		Yes		Yes
	Map Preview for location editing	No	No		No		Yes
	Rotate map symbols based on direction ²²	No	No		Yes		Yes
Cost		Included in ArcPad and TerraSync	\$75	\$199	\$199	\$199	\$349
					Can be bundled together for \$299		
Maintenance	Get free upgrades after original purchase	N/A	1 year standard – no extension available	90 days standard – no extension available	1 year standard - \$90 for additional year		90 days standard - \$99 for additional year
					Bundle additional year - \$120		

¹⁶ TerraSync data is exported to shapefile through GPS Pathfinder Office, ArcPad works directly with shapefiles, and GPS-Photo Link and Wind Image can output to shapefile.

¹⁷ TerraSync data is exported to multiple formats through GPS Pathfinder Office. ArcPad can only work in shapefiles.

¹⁸ If taken by the Ricoh 500SE or the Trimble Yuma, the original photo can be embedded with date, time and GPS information. Three additional memos can also be imprinted on photos taken with the Ricoh 500SE.

¹⁹ Photos can be renamed based on project, date and time. If taken by the Ricoh 500SE, file name can be based on Memo fields.

²⁰ ArcPad allows you to set a photo filename prefix so that you can control how the photos are named originally.

²¹ Wind Image and GPS Photo Link have photo editing built in. All other systems would depend on 3rd-party software.

²² If direction is recorded as an attribute in TerraSync or ArcPad, this could be done in ArcGIS. The Ricoh 500SE camera records the direction the photo was taken by using the GPS Tracklog, by entering the direction as an attribute Memo, or by reading attached compass.

Conclusions

Digital photos are an integral part of data collection for many applications. Managing the large amounts of data generated by GPS receivers and digital cameras can be challenging. Various methods are available to assist with this, and all have their pros and cons.

The ArcPad or TerraSync camera tool is easy to use in the field with a GPS with a built-in camera.

Wind Image Transfer now offers a solution easy WiFi transfer using Ricoh cameras, and TrimPix Pro offers a WiFi solution for most digital cameras.

The Ricoh 500SE camera is a truly field-worthy, rugged solution that can be used in conjunction with professional Trimble Mapping systems and software, or as a standalone data collection system.

The GPS-Photo Link software automates much of the process and includes many user-friendly features.

Wind Image for ArcMap and Wind Image StandAlone can be bundled together for a complete, user-friendly package with additional functionality at a lower cost.